

DADO™ GROOVED ABSORPTIVE WALL PANEL (AWP) ORDER CODE OPTIONS

PRODUCT	STYLE	PATTERN	Hole Pattern	OPEN AREA %	CORE RATING	NAUF	CORE MATERIAL	VENEER	FINISH	LENGTH	WIDTH	THICKNESS	FLEECE	FSC	OTHER
DADO	PN	XX/X/	S	(XX)	A	Y	MDF	AM	LA	(XX)	(XX)	(0.75)	BL	C	[XX]
	PL		C		N	N		AC	SL				NO	X	
	TL		N		H			WO	TV				WH		
								XX	UN						
								CSV	[PAINT#]						
								UN	[LAM #]						
								PT							
								LM							

Example:

Example 1: DADOPN14/2/12AYMDFAMLA(120)(48)(0.75)BLC - RPG® Grooved AWP, Panel, 14/2, Single diameter hole, 12% open area, Class A fire rating, NAUF, MDF core, American Maple veneer, Clear lacquer finish, 120" length, 48" width, 3/4" thickness, Black fleece, FSC mix 70%

Key:

PRODUCT

DADO - Grooved AWP

STYLE

PL - Plank

PN - Panel

TL - Tile

PATTERN

XX/X/ - Width of solid area (mm)/
width of groove (mm)

HOLE STYLE

S - Single diameter hole (std)

C - Custom hole configuration

N - No hole (reflective)

OPEN AREA

(XX) - Percent open area

CORE RATING

A - Class A fire Rated

N - Non Class A

H - High humidity

NAUF

Y - ULEF (NAUF pathway 2)

N - Standard Formaldehyde Content

CORE MATERIAL

MDF - Medium density fiberboard

VENEER

AM American Maple

AC - American Cherry

WO - White Oak

[XX] - Other veneer type

CSV - Customer supplied veneer

UN - Raw core material

PT - Painted

LM - Laminate

FINISH

LA - Clear lacquer

SL - Stain & clear lacquer

TV - Tinted varnish

UN - Unfinished

[RL] - RAL paint code

[LM] - Laminte order code

LENGTH

WIDTH

(XX) - Width in inches

THICKNESS (millimeters)

(0.75) - 3/4"

FLEECE

BL - Black

NO - None

WH - White

FSC

C - FSC Mix

X - Non FSC

OTHER

[XX] - Other feature code