

## Standard Unit Construction

Constituent materials conforming to the following ASTM specifications:

1. Portland Cement: ASTM C-150
2. Blended Cements: ASTM C-595
3. Hydrated Lime, Type S: ASTM C-270+
4. Aggregate: ASTM C-331 or C-33, based on local availability

Standard gray block aggregate color (actual color may vary)

12" deep block (dB12S and dB12NS):

7-5/8" height x 15-5/8" wide x 11-5/8" deep

8" deep block (dB8S and dB8NS):

7-5/8" height x 15-5/8" wide x 7-5/8" deep

dB8S and dB12S units contain a fiberglass insert

## Product Options\*, \*\*

### Models

dB12S: 12" deep DiffusorBlox® with a resonator slot.

dB12NS: 12" deep DiffusorBlox® without a resonator slot.

dB8S: 8" deep DiffusorBlox® with a resonator slot.

dB8NS: 8" deep DiffusorBlox® without a resonator slot.

### Color

DiffusorBlox® can be produced in a wide variety of colors. Please contact RPG® directly for more information.

### Aggregate

DiffusorBlox® can be produced in a wide variety of aggregates. Please contact RPG® directly for more information.

### Surface Texture

The back surface of DiffusorBlox® can be ground or textured. Please contact RPG® directly for more information.

## Option Sheet

### Note:

All dimensions are allowed a tolerance of  $\pm 1/16"$  due to material shrinkage and variations.

\* Most options merit an increase or, in some cases, a decrease in pricing compared to the standard unit.

\*\* Due to material availability, RPG® reserves the right to change options at any time. Therefore, any special options—whether listed or not—must be confirmed prior to submittal of P.O. and acceptance verified by RPG® Diffusor Systems, Inc.

