



# MATERIAL SAFETY DATA SHEET

for Diffusor Blox® Concrete Masonry Units

## 1. PRODUCT IDENTIFICATION

TRADE NAMES: (AS LABELED)	DIFFUSOR BLOX®
MANUFACTURER'S NAME:	RPG ACOUSTICAL SYSTEMS,
ADDRESS:	99 SOUTH STREET PASSAIC, NJ 06055
PHONE NUMBER:	(301)-249-0044
DATE PREPARED OR REVISED:	JULY 10, 2009
PREPARED BY:	JEFF MADISON

## 2. HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components: Silica, Crystalline Quartz (respirable)  
Specific Chemical Identity: Silicon Dioxide SiO<sub>2</sub> (CAS 14808-60-7)  
Common Names: Silica, Flint, Sand, Crystalline Free Silica, Quartz, Ground Silica, Silica Flour

OSHA PEL: Exposure to airborne crystalline silica shall not exceed an 8-hour time-weighted average limit as stated in 29 CFR 1910.1000 Table Z-1-A, Air Contaminants, specifically:

Silica, Crystalline Quartz (respirable Dust) 0.1 mg/M<sup>3</sup>

ACGIH TLV: Crystalline Quartz

TLV – TWA = 0.1 mg/M<sup>3</sup> (respirable Dust)

See Threshold Limit Value and Biological Exposure Indices for 1991-1992

American Conference of Governmental Industrial Hygienists

Other Limits Recommended: National Institute for Occupational Safety and Health (NIOSH). Recommended standard maximum permissible concentration = 0.05 mg/M<sup>3</sup> (respirable free silica) as determined by a full-shift sample up to a 10-hour work day, 40-hour work week. See NIOSH Criteria for a Recommended Standard Occupational Exposure to Crystalline Silica.

## 3. PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A                      Specific Gravity (H<sub>2</sub>O) = 1): N/A  
Vapor Pressure (mm Hg.): N/A                      Melting Point: N/A



Vapor Density (Air = 1): N/A                      Evaporation Rate (Butyl Acetate = 1): N/A  
Solubility in Water: Not Soluble  
Appearance and Odor: Odorless Solid

---

#### 4. FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A  
Flammable Limits: N/A                      LEL: N/A                      UEL: N/A  
Extinguishing Media: N/A  
Special Fire Fighting Procedures: None  
Unusual Fire and Explosion Hazards: None

---

#### 5. REACTIVITY DATA

Stability: [ ] Unstable: [ ] Stable: [ X ]                      Conditions to Avoid: None  
Incompatibility (Materials to Avoid): None  
Hazardous Decomposition or Byproducts: None  
Hazardous Polymerization: May Occur: [ ] Will Not Occur: [ X ] Conditions to Avoid: None

---

#### 6. HEALTH HAZARD DATA

Route(s) of Entry:  
Inhalation? Yes                      Skin: No                      Ingestion? Yes

##### Health Hazards (Acute and Chronic):

Dry sawing or grinding of concrete masonry products may result in the release of respirable crystalline quartz. Prolonged exposure to respirable crystalline quartz may cause delayed (chronic) lung injury (silicosis). Acute or rapidly developing silicosis may occur in a short period of time in heavy exposure. Silicosis is a form of disabling pulmonary fibrosis which can be progressive and may lead to death.

##### Carcinogenicity:

NTP? Yes

The National Toxicology Program (NTP) published its Sixth Annual Report on Carcinogens which concludes that "silica, crystalline (respirable)" may reasonably be anticipated to be a carcinogen. The NTP conclusion is based on sufficient evidence for the carcinogenicity of respirable crystalline silica in experimental animals and limited evidence in humans.

IARC Monographs? Yes

IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Humans (volume 42, 1987) concludes that there is sufficient evidence for the carcinogenicity of crystalline silica



to experimental animals, and that there is limited evidence of the carcinogenicity of crystalline silica to humans. IARC Class 2A.

Signs and Symptoms of Exposure: Undue breathlessness, wheezing, cough and sputum production.

Medical Conditions Generally Aggravated by Exposure:

Pre-existing lung diseases such as emphysema or asthma. Pulmonary function may be reduced by inhalation of respirable crystalline silica. Also lung scarring produced by such inhalation may lead to progressive massive fibrosis of the lung which may aggravate other pulmonary conditions and diseases and which increases susceptibility to pulmonary tuberculosis. Progressive massive fibrosis may be accompanied by right heart enlargement, heart failure, and pulmonary failure. Smoking aggravates the effects of exposure.

Emergency and First Aid Procedures:

For sand in eyes during dry sawing or grinding operations, immediately flush generously with water for 15 minutes. If irritation persists, seek medical attention. For gross inhalation, remove person immediately to fresh air, give artificial respiration as needed, and seek medical attention as needed.

---

## 7. PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in Case Material is Released or Spilled:

When dry sawing or grinding, use dustless systems for handling, storage, and clean-up so that airborne dust does not exceed the PEL. Use adequate ventilation and dust equipment. Practice good housekeeping. Do not permit dust to collect on walls, floors, sills, ledges, machinery, or equipment. Maintain, clean, and fit test respirators in accordance with OSHA regulations. Maintain and test ventilation and dust collection equipment. Wash or vacuum clothing which has become dusty. See also control measures in Section VIII.

Waste Disposal Method:

Normal breakage may be picked up and discarded as common waste. Residue from dry sawing and grinding operations should be disposed of in accordance with Federal, State, and Local regulations.

Precautions to be Taken in Handling and Storing: None

Other Precautions:

See OSHA Hazard Communication Rule 29 CFR Sections 1910.1200, 1915.00., 1917.28, 1918.90, 1926.59, and 1928.21 and state and local worker or community "right to know" laws and regulations. We recommend that smoking be prohibited in all areas where respirators must be used. **WARN YOUR EMPLOYEES (AND YOUR CUSTOMERS – USERS IN CASE OF RESALE) BY POSTING, AND OTHER MEANS, OF THE HAZARD AND OSHA**



PRECAUTIONS TO BE USE USED. PROVIDE TRAINING FOR YOUR EMPLOYEES ABOUT THE OSHA PRECAUTIONS.

See also American Society for Testing and Materials (ASTM) Standard Practice E1132-86, "Standard Practice for Health Requirements Relating to Occupational Exposure to Quartz dust."

## 8. CONTROL MEASURES

### Respiratory Protection

The following chart specifies the type of respirators which may provide respiratory protection for crystalline silica.

#### RESPIRATORY PROTECTION FOR CRYSTALLINE SILICA

CONDITION Particulate Concentration	MIMINUM RESPIRATORY PROTECTION*
Up to 5 x PEL	Any dust respirator.
Up to 10 X PEL	Any dust respirator, except single-use or quarter-mask respirator. Any fume respirator or high efficiency particulate filter respirator. Any supplied-air respirator. Any self-contained breathing apparatus.
Up to 50 X PEL	A high efficiency particulate filter respirator with a full face piece. Any supplied-air respirator with a full face piece, helmet, or hood. Any self-contained breathing apparatus with a full face piece.
Up to 500 X PEL	A power air-purifying respirator with a high efficiency particulate filter. A type C supplied-air respirator operated in pressure-demand or other positive pressure or continuous-flow mode.
Greater than 500 X PEL or entry and escape from unknown concentrations	Self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive mode.  A combination respirator which includes a Type C supplied-air respirator with a full face piece operated in pressure-demand or other positive pressure continuous-flow mode and an auxiliary self contained breathing apparatus operated in pressure-demand or other positive pressure mode.

\*Only NIOSH-approved or MSHA-approved equipment should be used. \*See 29 CFR 1910.134).



See also ANSI Standard Z88.2 – 1980 “Practices for Respiratory Protection.”

Ventilation:

Local Exhaust:

When dry sawing or grinding concrete masonry products, use sufficient local exhaust to reduce the level of respirable dust to the PEL. See ACGIH “Industrial Ventilation, A Manual of Recommended Practice,” latest edition.

Mechanical:

See “Other Precautions” Under Section VII

Special:

See “Other Precautions” Under Section VII

Other:

See “Other Precautions” Under Section VII

Protective Gloves:

Optional

Eye Protection:

When sawing or grinding concrete masonry products, wear protective shield or tight fitting goggles (safety glasses).

Other Protective Clothing or Equipment:

Optional

Work/Hygienic Practices:

Avoid creating and breathing dust. See “Other Precautions” under Section VII.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to airborne dust particles created by dry sawing or grinding of our products. Customers/users of concrete masonry products must comply with all applicable health and safety laws, regulations, and orders.