



MATERIAL SAFETY DATA SHEET

for Fabric-Wrapped Wood Based Modex Products with Fiberglass Infill

1. PRODUCT IDENTIFICATION

| | |
|---------------------------|---|
| TRADE NAMES: (AS LABELED) | MODEX™ CORNER MODEX™ LF PANEL MODEX™ MODULE |
| MANUFACTURER'S NAME: | RPG ACOUSTICAL SYSTEMS, LLC. |
| ADDRESS: | 99 SOUTH ST. PASSAIC, NJ 07055 |
| PHONE NUMBER: | (973)-916-1166 |
| DATE PREPARED OR REVISED: | APRIL 18, 2017 |

2. HAZARDOUS INGREDIENTS

| CHEMICAL NAMES | CAS # | PERCENT | AGENCY | EXPOSURE LIMITS |
|------------------------|------------|-------------------|--------------|---|
| FORMALDEHYDE | 50-00-0 | < 0.05% by weight | OSHA | PEL-TWA 0.75ppm PEL-STEL 2.0 ppm |
| | | | ACGIH | TLV-CEILING 0.3 ppm* |
| LIGNO-CELLULOSIC FIBER | None | Proprietary | OSHA | PEL-TWA 15.0 mg/m ³ (total) 5.0 mg/m ³ (respirable fraction) |
| | | | ACGIH | TLV-TWA 1.0 mg/m ³ |
| FIBROUS GLASS | 65997-17-3 | < 50% by weight | OSHA | PEL 5.0 mg/m ³ |
| | | | ACGIH | TLV 10.0 mg/m ³ |
| CYCLOHEXANE | 110-82-7 | Negligible | OSHA + ACGIH | TWA 300 ppm |
| N-HEXANE | 110-54-3 | Negligible | OSHA + ACGIH | TWA 50 ppm |
| ACETALDEHYDE | 75-07-0 | Negligible | | |

* Based on sensory exposure

3. HAZARD IDENTIFICATION

Overview: The panel may release small quantities of formaldehyde in gaseous form. Emissions decrease through time as the panel ages. Manual or mechanical cutting processes performed on the panel can result in generation of ligno-cellulosic and glass fiber dust.

Primary Health Hazards: Ligno-cellulosic fiber, glass fiber and formaldehyde dust.



Primary Route(s) of Exposure:

Ingestion: Not applicable.

Skin: Wash affected areas with soap and rinse with large amounts of water. Get medical attention if rash or irritation persists or dermatitis occurs.

Inhalation: Fiber dust may cause unpleasant obstruction in the nasal passages, resulting in dryness of nose, dry cough, sneezing and headaches. Remove to fresh air. Get medical attention if irritation persists, severe coughing or breathing difficulty occurs.

Eye: Fiber dust may cause mechanical irritation. Treat dust in eye as foreign object. Flush eyes with large amounts of water. Remove to fresh air. If irritation persists, seek medical attention.

Medical Conditions Generally Aggravated by Exposure: Fiber dust or formaldehyde may aggravate pre-existing respiratory conditions or allergies.

Disposal: Dispose of panels in accordance with federal, state and local regulations. The primary method of disposal is in an industrial landfill.