



Blue = Expo Panel + 1", 6lb/ft³ fiberglass board - NRC = 0.75, SAA = 0.75
 Green = Expo Panel + 2", 6lb/ft³ fiberglass board - NRC = 0.80, SAA = 0.80

Additional test data is available – please see the Supplementary Acoustical Data Charts online or contact your local RPG Sales Representative.

Frequency (Hz)	W/2", 6lb/ft ³ Fiberglass Insul.
100	0.44
125	0.52
160	0.62
200	0.60
250	0.81
315	0.86
400	0.88
500	0.90
630	0.91
800	0.87
1000	0.77
1250	0.77
1600	0.73
2000	0.74
2500	0.71
3150	0.70
4000	0.67
5000	0.71
NRC	0.80
SAA	0.80

PRODUCT OVERVIEW

The **Expo™ 45 Panel** is the ultimate synergy between acoustical technology and architectural panel design using an optimal binary pattern of round perforations. They are available in a high recycled content, ULEF, Class A fire-rated ULEF and FSC certified wood panel MDF core with an optional black fleece backer. The **Expo™ 45 Panel** achieves an excellent balance of sound absorption across the NRC frequency bands while preserving the space's ambiance with high-frequency diffusion.

SIZING

- Standard Panel: 4' W x 8' L x 3/4" T
- Maximum Panel: 5' W x 12' L x 3/4" T
(Custom panel widths and lengths are available)
- Perforation Panel Styles: 45 (shown), Cells, Code, Galaxy, and Standard. Custom profiles available upon request.
- Open Area: Approx. 21%
- Planks with T & G long edges can be provided in lieu of panels. Plank widths to be finalized during the submittals process.
- Each panel weighs approx. 2.00 lbs/ft²

CORE FIRE RATING

Class A (per ASTM E 84)

FINISH

The **Expo™ 45 Panel** is available various finishes, including natural and engineered wood veneers and laminates. RPG offers clear lacquer or color-matching of both wood finishes and paint colors.

INSTALLATION

Mounting options for the **Expo™ 45 Panel** include wall systems (Z-clips, direct screw attached), either surface mounted or with a variety of cavity depths starting at 1-3/4" total system depth or ceilings systems (Torsion Springs for downward access, RPG C-clips for lift and shift access, direct screw attached) and options for 15/16" HD T-grid supplied by others.