



SoniQ™ Oak 101 - RC



SoniQ™ Oak 101 - PS



SoniQ™ Walnut 201 - PS

PRODUCT OVERVIEW

The Perfecto® Micro Quick Ship Program (QSP) delivers ready-to-install panels within 2 weeks of order release. Stock panels can be trimmed and edged in the field with matching pre-finished edge banding due to RPG's proprietary Flex™ core. The Flex™ core design allows the panel to be cut down with clean edges for edge banding. It also allows factory conversion of stock panels to TNG Planks with an average 2-4 weeks added lead time. **Perfecto® Micro QSP** utilizes hundreds of thousands of nominal 0.4mm laser perforations to efficiently absorb a broad range of sound frequencies, achieving NRC ratings up to 0.95. Panels have high recycled content and are ULEF, FSC, and Class A fire-rated.

SIZING

- Standard Panel: 4' W x 8' L x 3/4" T
- Plank Option: Nominal 6" W x 8' L x 3/4" T
- Wood panels weigh approx. 1.50 lbs/ft²

CORE FIRE RATING

Class A (per ASTM E-84)

FINISH

The **Perfecto® Micro QSP** features three options in natural, reconstituted wood veneers with a clear lacquer finish: SoniQ™ Oak 101 - PS, SoniQ™ Oak 101 - RC and SoniQ™ Walnut 201 - PS (see images at left). Reconstituted veneers are among the best choices for eco-friendly alternatives in the building industry today. They are sourced from fast-growing, sustainably managed wood species, which reduces pressure on old-growth forests, and they are well known for their benefits, including uniform appearance, freedom from defects and reduced waste.

INSTALLATION

Mounting options for the **Perfecto® Micro QSP** include wall systems (Z-clips, direct screw attached), either surface-mounted or with a variety of cavity depths starting at 1-3/4" total system depth, or ceiling systems (Torsion Springs for downward access, RPG C-clips for lift and shift access, direct screw attached) with options for standard 15/16" HD T-grid supplied by others.