



Blue = A-mount, 1" air cavity
 Green = D-Mount, 2" air cavity
 Red = A-Mount, 1" 6lb/ft³ fiberglass board
 Purple = D-Mount, 2" 6lb/ft³ fiberglass board

Additional test data is available – please see the Supplementary Acoustical Data Charts online or contact your local RPG Sales Representative.

Frequency (Hz)	D-Mount W/2" 6lb/ft³ Fiberglass Insul.
100	0.31
125	0.42
160	0.65
200	0.84
250	0.75
315	0.92
400	0.98
500	0.99
630	1.04
800	1.01
1000	0.99
1250	0.95
1600	0.91
2000	0.94
2500	0.92
3150	0.79
4000	0.70
5000	0.63
NRC	0.95
SAA	0.94

PRODUCT OVERVIEW

The **Parallels™ DITTO** is manufactured with a wood veneer facing on black fire-rated MDF blades secured to a continuous high-density PET acoustical backer. **Parallels™ DITTO** is designed to be installed on walls and is available standard in wood veneer with an optional FSC®-certified core when required. An NRC of 0.75 - 0.95 is achievable with our standard mounting details.

SIZING

- Standard Panel: 2' W x 8' L x 2-1/4" D (Actual length 1" under the foot) (Custom lengths are available)
 - Blade Thickness: 3/4"
 - Blade Widths: 1-3/8"
 - Standard Reveal: 1"
 - Blades/2' Panel Width: 10
 - Each panel weighs approx. 3.00 lbs/sf
- Note: Custom module sizes are available

CORE FIRE RATING

Veneer: Class A (per ASTM E-84) component throughout
 Solid Wood: Standard product not rated.
 Class A (per ASTM E-84) finish available if specified.

FINISH

Choose from a wide variety of standard and exotic veneer species available on the market. Our veneer specialists can help you with your selection. The blades can be finished with our standard low-sheen clear lacquer, providing durable protection that highlights the wood's natural beauty. Alternate options include using solid wood blades and custom color matching of wood finishes and paint colors.

INSTALLATION

The standard mounting option for the **Parallels™ DITTO** is a surface-mounted wall system with RPG-provided wood cleats.